



Government of Goa
DIRECTORATE OF SKILL DEVELOPMENT & ENTREPRENEURSHIP
FARMAGUDI GOVERNMENT INDUSTRIAL TRAINING INSTITUTE
Farmagudi-Ponda-Goa, 403401
Ph: (0832) 2980070

Website: www.itifarmagudi.goa.gov.in Email: farmagudi-iti.goa@nic.in
Ref.No:114/FGD/ITV/STR/Sewing Machine(DM)/STRIVE 2021/ **4655** Dated: **06/11/2021**

To,
Website
O/o Farmagudi Industrial Training Institute,
Farmagudi-Ponda-Goa, 403401.

Sub :- Inquiry for Sewing Machine Electrically Operated reg...

Sir,


Quotation is invited in sealed envelope as per the specification and quantity mentioned below:-

Sr. No	Items/ Specifications	Qty	Unit Nos/Kg	Rate per unit Rs.	Taxes	Amount Rs.
	As per Annexure - Sewing Machine Industrial Model					
Total amount						
Taxes						
Grand Total						

The terms and conditions for the supply shall be as under:-

1. The material shall be supplied for destination within 10 days of placing supply order at Farmagudi Industrial Training Institute, Farmagudi, Ponda- Goa.
2. GST and any other levy applicable at the time of quotation may be shown separately in the quotations; otherwise it will be presumed that the prices offered are inclusive of all taxes.
3. The rate quoted shall be inclusive of packing & forwarding charges freight paid for destination Farmagudi Industrial Training Institute, Farmagudi, Ponda- Goa.
4. The quotations shall be valid for 45 days from the date of the opening of the same.
5. The quotation will be evaluated for all the items together. Therefore, all the items may be quoted.
6. The materials if not accepted after inspection shall be collected by the supplier immediately with written assurance to supply the same as per the specifications as mentioned in the supply order. The Farmagudi Industrial Training Institute, Farmagudi, Ponda- Goa, shall not be responsible for security/ storing.
7. This office reserves the right to accept or reject any quotations without assigning any reason thereof.
8. The warranty/guarantee shall be furnished with the item as the case may be.
9. The extension of limit will be granted at the discretion of I.T.I. on genuine grounds by the written request of the supplier.
10. The quotation should reach this office on or before **06/12/2021** at 2.30 P.M. either by return e-mail, hand delivery or by post and will be opened on same day i.e. on 06/12/2021 at 3.30 P.M.


Yours faithfully,


(S. S. Gaonkar)
Principal(Sr Scale)

Copy to 1) The Account Section, Farmagudi, Govt.I.T.I., Farmagudi, Ponda- Goa
2) O/c

ANNEXURE- FOR SEWING MACHINE INDUSTRIAL MODEL DRESS MAKING

Sr. No.	Items with Specification	Qty Req.	Rate per Unit	Total Amount in Rs.
1	<p>(i) Sewing mechanism that demonstrates responsiveness to materials to be sewn. The sewing mechanism should achieve low-tension sewing, the machine should respond to various kinds of materials and produces beautiful seams of consistent quality.</p> <p>(ii) The machine should be designed to reduce vibration and noise and upgrade reliability and durability By adopting a machine frame structure designed to obtain optimal balance and upgrade strength and rigidity , the machine should run with reduced vibration and noise.</p> <p>(iii) The machine should have easy –to-operate functions to achieve improved operability. Provide a presser foot with a higher lift(13mm), a light-touch stitch dial, and other easy-to operate functions, the burden on the operator should be lightened ,and productivity increased.</p> <p>The hand pulley should be designed to contain a deep, recess to allow the operator to hold the pulley firmly and turn it with ease.</p> <p>(iv) The machine should be standard with attachment mounting seats. The machine should be standard with extra attachment mounting seats for attachment of new auxiliary parts in the future. The extremely high durability of the seats ensures an extended service with frequent replacement of attachments.</p> <p>(v) The location of the hinge to prevent the sewing material from being caught by the hinge. The hinge should be located as such so as to prevent the material from being caught by it, thereby improving workability.</p> <p>(vi) Application Light to medium weight</p> <p>(vii) Max.sewing speed 4000 sti/min* and above</p> <p>(viii) Max. stitch length 5mm</p> <p>(ix) Needle bar stroke 30.7mm</p> <p>(x) Lift of the Presser foot By hand: 5.5mm, By Knee: 13mm</p> <p>(xi) Needle DB x 1 (#14) #9 ~ #18</p> <p>(xii) Feed dog 3 row</p> <p>(xiii) Hook Automatic lubricating full rotary hook</p> <p>(xiv) Lubrication Automatic</p> <p>(xv) Lubricating Oil No. 7 (equivalent to ISO VG7)</p> <p>(xvi) Weight of machine head 26 kg and above</p>	10 Nos.		


 (S. S. Gaonkar)
 Principal Sr. Scale
 Farmagudi Govt.ITI