









## Government of Goa

## DIRECTORATE OF SKILL DEVELOPMENT & ENTREPRENEURSHIP FARMAGUDI GOVERNMENT INDUSTRIAL TRAINING INSTITUTE

Farmagudi-Ponda-Goa, 403401 Ph :- (0832) 2980070

276/FGD/ITI/STR//2025/Hydraulic Trainer Kit (F)/2025/ 己ママリ

Website: www.itifarmagudi.goa.gov.in Email: farmagudi-iti.goa@nic.in Dated: ペラ/

**0** S /2025

9

Website

Sub :- Inquiry of Hydraulic Trainer Kit for Fitter Trade reg..

Si

at the lowest rates :-Quotation is invited in sealed envelope from the reputed supplier to supply the enclosed list of items

		Sr. No			
	As per attached Annexure	Items/ Specifications			
		Š.			
		Unit Nos/Kg			
Tota		Rate per unit			
Total amount		Amount			
		Amount Remarks.			

## The terms and conditions for the supply shall be as under:-

- The material shall be supplied for destination within 45 days of placing supply order at Farmagudi Government ITI, Farmagudí, Ponda-Goa.
- N GST any other levy applicable at the time of supply may be shown separately in the quotation otherwise if will be presumed that the prices offered are inclusive GST.
- ယ The quotations shall be valid for 90 days from the date of the opening of the same
- 4 Farmagudi Industrial Training Institute, Farmagudi, Ponda- Goa The rate quoted shall be inclusive of packing & forwarding charges freight paid for destination
- Ġ in the supply order. The material will be accepted after inspection only if the same confirms with the specification mentioned
- $\circ$ may be quoted. The quotation will be evaluated for all the items together. Therefore, all the items
- written assurance to supply the same as per specifications as mentioned in the supply order The material if not accepted after the inspection shall be collected by the supplier immediately with
- $\infty$ security/storing Farmagudi Industrial Training Institute, Farmagudi, Ponda-Goa, shall not be responsible ğ
- 9 This office reserves the right to accept or reject any of the quotations without assigning any reason
- 10. The warranty/guarantee shall be furnished with the item as the case may be
- 11. The extension of time limit will be granted at the discretion of I.T.I. on genuine grounds by the written request of the supplier.
- 12. Part supply of the order shall be furnished as the case may be. [2]
- 13. The quotation should reach to this office on or before  $\mathbb{Z}_{\mathbb{R}}$   $\mathbb{Z}_{\mathbb{R}}$ mail, hand delivery or by post and will be opened on same day i.e. on 🎾 👍 🖒 🚉 at 3:30 p.m. at 2:30 p.m. either by return e

MINIMAN AND MARKET

Yours faithfully

Principal (Sr. Scale)

(Akshay A. Shiwaikar)

Sr. no.	Hydraulic trainer kit	11 224
D1. HU.		1 set
	Hydraulic trainer kit, each consisting of the following matching components and accessories Confirming to ISO/ ISI Standards.	1 set
	I. Hydraulic power pack with (1) external gear pump having a	l no.
	delivery rate of 2051 mp, 1400 rpm & operating pressure of 60,	
	bar, coupled to a single phase AC motor (230 V AC )having start	
	capacitor, ON/OFF switch and overload protection. (2) pressure	
	relief valve adjustable from 0 – 60 bar, (3) Oil reservoir of 5 liters capacity having sight glass drain screw, air filter and P and T ports	
	II .Pressure relief valve pilot operated	l no.
	III. Drip tray of steel, size 1160 X 760 mm	1 no.
	IV. Pressure gauge ,Glycerin damped with indication range of 0 -	l no.
1	100 bar	
	V. Four way distributor with Five ports, equipped with pressure	l no.
	gauge	
	VI. Double acting hydraulic cylinder with a control cam, piston	l no.
	diameter 16 mm, piston rod diameter, 10 mm and stroke length 200	
	mm	
	VII. Suitable weight for vertical loading of hydraulic cylinder	1 no.
	VIII. Mounting kit for weight for realizing, pulling and pushing	l no.
	load.	
	IX. 3/2 – way directional control valve with hand lever actuation.	1 no
4.	X. 4/2 - way directional control valve with hand lever actuation.	1 no.
	XI.4/3 - way directional control valve with closed - Centre	l no.
	position, with hand lever actuation.	
	XII. Non return valve	1 no.
	XIII. Pilot operated check valve with pilot to open	l no.
	XIV. One way flow control valves with integrated check valve.	l no.
	XV. T- Connector with self-sealing coupling nipples (2 nos.) and	2 nos.
	quick coupling socket (1 no)	
	XVI. Profile plate. Anodized aluminum, 1100 X 700 mm, with	1 set
	carriers, mounting frames and mounting accessories (to be fitted on	
***************************************	to the hydraulic workstation)	
	Hydraulic workstation with 40 square mm aluminum profile legs,	1 no.
•	wooden work surface and one pedestal drawer unit having 5	
2	drawers each with handles and individual locks, on metallic full	
	panel drawers slides: (1) Work table – size L 1200mm X W900mm	
	XH 900mm, with four caster wheels including two lockable wheels	
	at the front side, (2) drawer size (approx) – L460mm X W 495mm	
	X H158mm each ,and overall size of drawers size unit (approx.)	
	L470 X W495mm X H825 and (3) Drawers slide height (approx.)85mm	į
	(approx.)onitiii	
	Cut – Section models for hydraulic components	1 Set
	22. 2441011 111014110 101 117 diamin Antihonomo	1 705